

DOWNLIGHT 10W SERIES ARTIVIA - 075H1 LOOX PLUS

OVERVIEW

The Downlight 10W is a compact recessed LED luminaire designed to provide comfortable, balanced general lighting with a clean architectural ceiling appearance. Its discreet design helps illuminate smaller interior areas efficiently without overcrowding the ceiling, making it ideal for hotel corridors, guest-room entrances, residential hallways, office circulation areas and small commercial spaces.

PRODUCT VARIANTS & TECHNICAL DATA

Code	Type / Description	Wattage(W)	Total Luminous Flux(lm)	Luminous Efficacy(lm/W)	Power Factor(pf)	Beam Angle	CRI (Ra)	IP Rating
LD18710G103	3000K, Gray, إضاءة نازلة داون لايت, Eaglerise Driver	10W	1000	100	>0.5	36°	>90	54

TECHNICAL INFORMATION

Frequency	50-60 Hz
Input Voltage	220-240 VAC
Life Span	50000 H
Protection class	Class II
SDCM	≤ 5
Ambient temperature(Ta)	-15℃+55℃
Operating temperature	-15℃+45℃
UGR	<17
Product Face Size (mm)	88*60
Product Weight (gr)	169
Energy Usage	A+
Lumen Maintenance (L70)	1000

INSTRUCTION

Instruction Manual	

GENERAL INFORMATION

Body Material	Die-Cast Aluminum
Diffuser	PC
Reflector	PC
Mounting Type	Recessed
Cut Size	Φ70mm
Driver Brand	Eaglerise/Philips
Chip Brand	Osram/Bridgelux
LED Type	COB

APPLICATION AREAS

- Hospitality: Hotel Corridors, Lift Lobbies, Reception Areas, Waiting Zones, Guest-Floor Circulation
- Residential Building: Entrances, Hallways, Dressing Areas, Feature Walls, Artwork Areas, etc.
- Commercial Buildings: Reception Areas, Entrance Halls, Internal Corridors, Waiting Areas, Lift Lobbies