





FLOOD LIGHT 100W TITAN SERIES LOOX

OVERVIEW

Titan Series LED Flood Light provides reliable performance, great visibility and a better than expected lighting experience. The luminaire offers a wide range of power and CCTs to meet different requirements of application.

PRODUCT VARIANTS & TECHNICAL DATA

Code	Type / Description
LIF1TI01003	3000K, إضاءة فيضانات فلودلايت, On/Off Driver
LIF1TI01004	4000K, إضاءة فيضانات فلودلايت, On/Off Driver
LIF1TI01006	6500k, إضاءة فيضانات فلودلايت, On/Off Driver
LIF1TID1003	3000K, إضاءة فيضانات فلودلايت, Dimmable Driver
LIF1TID1004	4000K, إضاءة فيضانات فلودلايت, Dimmable Driver
LIF1TID1006	6500k, إضاءة فيضانات فلودلايت, Dimmable Driver

TECHNICAL INFORMATION

Frequency(Hz)	50-60
Input Voltage(V)	220-240V
Product Face Size (mm)	303*220*52
Product Weight (gr)	1500
Life Span(Hrs)	50000
IK	08
Surge Protection(KV)	10
Protection Class	II
SDCM	3
Sensor	No
Ambient Temperature(Ta)	-40°C to 50°C
Energy Usage	A+
UGR	<17

GENERAL INFORMATION

Body Material	Diecast Aluminum
Diffuser	Glass
Mounting Type	Surface
Driver Brand	Lifud
Chip Brand	Lumiled
Light Source	
Cable & Gland Type	
Reflector	
Cut Size	

APPLICATION AREAS

- Hotel and Resorts
- Parking & Access Areas
- Villa Walkways
- Garages and Workshops
- Landscape & Public Areas
- Commercial & Industrial Areas
- Mosques & landmarks
- Hospitality & Residential
- Industrial & Storage Facilities