

SMD DOWNLIGHT 36W LOOX

OVERVIEW

A round recessed ceiling fixture for general indoor lighting. Its frosted diffuser softens and spreads light, while the flush white trim keeps the ceiling visually uncluttered. It suits libraries, office buildings, and retail stores.

PRODUCT VARIANTS & TECHNICAL DATA

Code	Type / Description	Wattage(W)	Total Luminous Flux(lm)	Luminous Efficacy(lm/W)	Power Factor(pf)	Beam Angle	CRI (Ra)	IP Rating
LPD10010363	2700K, إضاءة نازلة داون لايت, Eaglerise Driver, IP20	36	3600	100	>0.95	110°	>80	20

TECHNICAL INFORMATION

Frequency(Hz)	50- 60
Input Voltage(VAC)	220-260
Life Span(Hrs)	50000
IK	08
Sensor	No
Ambient temperature(Ta)	-20° , +50°
Operating temperature	-20° , +50°
Product Face Size (mm)	228*46
Product Weight (gr)	700
Energy Usage	A+
Lumen Maintenance(lm)	3600

INSTRUCTION

Instruction Manual	

GENERAL INFORMATION

Body Material	Aluminum
Mounting Type	Recessed
Cut Size	200
LED Type	SMD

APPLICATION AREAS

- Retail Store — Merchandise display tables, display plinths, checkout counters.
- Hotel — Reception counters, lobby display tables, guest-room luggage benches
- Residential — Entryway consoles, kitchen islands, decorative display niches.