



STRIP LIGHT 2835 120 24V LOOX

OVERVIEW

High Brightness: 120 LEDs per meter provide smooth, continuous light with minimal spotting.
24V DC Operation: Lower voltage drop, making it suitable for longer installation lengths.
Energy Efficient: Delivers excellent illumination while consuming less power.
Flexible & Easy to Install: Can be bent around curves and cut at designated points for customized installations.
Long Service Life: Reliable LED technology ensures long-lasting performance with minimal maintenance.
Wide Applications: Ideal for cove lighting, shelves, cabinets, display cases, hotels, offices, homes, and retail environments.

PRODUCT VARIANTS & TECHNICAL DATA

Code	Type / Description	Wattage(W)	Total Luminous Flux(lm)	CRI (Ra)	IP Rating
LR283021201	3CCT, 8mm, 2 years, إضاءة شريطية	10	24/LED	>70	20

TECHNICAL INFORMATION

Power Factor(Pf)	>0.5
Voltage(V)	24
Frequency(Hz)	50
IK	
SDCM	<6
Ambient Temperature(Ta)	
Life Time(Hrs)	30000
Total Luminous Flax(lm)	24/LED
Product Size(mm)	

GENERAL INFORMATION

PCB Base (Copper or Iron)	Copper
PCB Width(mm)	
Thickness(mm)	8
Cutting Length(M/CM)	5M
Cut Size(M/CM)	5CM
LED Qty(pcs)	120
DOB	
Mounting Type	Surface Mounted

APPLICATION AREAS

- Education
- Car Parking
- Retail
- Residential
- Industrial & Storage