



GLASS T8 TUBE 70W 1.2M(SILVER BASE) LOOX

OVERVIEW

high-efficiency lighting solution designed to provide bright, uniform illumination while reducing energy consumption. With a 30,000-hour lifespan, it offers long-lasting performance and low maintenance costs, making it ideal for commercial, industrial, and residential applications.

PRODUCT VARIANTS & TECHNICAL DATA

Code	Type / Description	Wattage(W)	Total Luminous Flux(lm)	Luminous Efficacy(lm/W)	Power Factor(pf)	Beam Angle	CRI (Ra)	IP Rating
LKT12G10703	3000K, إضاءة انبوب	70W	6300	90	>0.5	280°	>70	20

TECHNICAL INFORMATION

Frequency(Hz)	50-60
Input Voltage(V)	220-260
Life Span(Hrs)	30000
IK	
Surge Protection(KV)	
Protection Class	
SDCM	4>
Sensor	No
Ambient Temperature(Ta)	-20° , +50°
Operating Temperature	-20° , +50°
UGR	
Product Face Size (mm)	1200
Product Weight (gr)	
Energy Usage	A+
Lumen Maintenance(lm)	6300

DIMENSION DRAWINGS



GENERAL INFORMATION

Body Material	Glass
Diffuser	
Reflector	
Mounting Type	Holder
Cut Size	
Driver Brand	
Chip Brand	
LED Type	

APPLICATION AREAS

- Schools
- Car Parking
- Warehouses
- Residential Building
- Commerical Buildings

3 YEARS GUARANTEE
ISO 9001:2005
CE
ISO 14001:2015