



STRIP LIGHT 2835-120 8MM STICKER TYPE LOOX

OVERVIEW

This economical single-line LED strip light operates at 14 W/m and provides a luminous flux of 1260 lumens/m, with an efficiency of up to 90 lumens/watt. It features a copper base and adhesive strip, and can be cut every 10 cm.

Operating at 220V, it is suitable for use in homes, hotels, malls, and offices. It is IP65 waterproof, allowing for use in both indoor and outdoor environments.

PRODUCT VARIANTS & TECHNICAL DATA

Code	Type / Description	Wattage(W)	Total Luminous Flux(lm)	Luminous Efficacy(lm/W)	CRI (Ra)	IP Rating
LRD3502711B LRD3502711G LRD3502711M LRD3502711R LRD35027113 LRD35027114 LRD35027116	BLUE / GREEN / MANGO / RED / 2700K / 4000K / 6500K, 10cm Cut, 10m, Strip Light	14	1260	90	>70	65

TECHNICAL INFORAMTION

Power Factor(Pf)	
Voltage(V)	220-240
Frequency(Hz)	50
IK	
SDCM	6>
Ambient Temperature(Ta)	-20° , +50°
Life Time(Hrs)	50000
Total Luminous Flax(lm)	1260
Product Size(mm)	

GENERAL INFORMATION

PCB Base (Copper or Iron)	Copper
PCB Width(mm)	
Thickness(mm)	8
Cutting Length(M/CM)	10M / 50M
Cut Size(M/CM)	10CM
LED Qty(pcs)	120
DOB	Yes
Mounting Type	Surface

APPLICATION AREAS

- Schools
- Car Parking