



PANEL 60W 60*60 BACKLIGHT LOOX

OVERVIEW

A ceiling lighting solution designed for indoor spaces. It provides broad, even illumination to support everyday activities. Its slim, unobtrusive design blends neatly into ceilings while creating a consistently lit surface. Suitable for offices, classrooms, retail spaces and reception areas.


PRODUCT VARIANTS & TECHNICAL DATA

Code	Type / Description	Wattage(W)	Total Luminous Flux(lm)	Luminous Efficacy(lm/W)	Power Factor(pf)	Beam Angle	CRI (Ra)	IP Rating
LPP1B620603 LPP1B620604 LPP1B620606	2700K / 4000K / 6500K, SQUARE, Panel Light	60	6000	100	>0.5	180°	>80	20

TECHNICAL INFORMATION

Frequency(Hz)	50
Input Voltage(V)	165-265
Life Span(Hrs)	25000
SDCM	<5
Sensor	No
Ambient Temperature(Ta)	-10°C ~ +40°C
Product Face Size (mm)	595*595
Energy Usage	A+
Lumen Maintenance(lm)	6000

DIMENSION DRAWINGS



GENERAL INFORMATION

Body Material	Aluminium
Diffuser	PS
Mounting Type	Recessed
Chip Brand	Sanan

APPLICATION AREAS

- Schools: classrooms, libraries and administrative offices.
- Commercial Buildings: workspaces, meeting rooms and reception areas.